



Stand-Alone Multifunctional Version





Code	Input Voltage	LED Type	Input Power	Lumen	Duration	Battery	Sensor	Dimensions (ΦxH)
SCN-900	220-240V ~ 50/60Hz	SMD2835	9 W	900/450 Lm	—	—	—	Φ267x57 mm
SCN-900S	220-240V ~ 50/60Hz	SMD2835	10.5 W	900/450 Lm	—	—	Yes	Φ267x57 mm
SCM-1500	220-240V ~ 50/60Hz	SMD2835	15 W	1500/1000/700 Lm 270 Lm	—	—	—	Φ335x63 mm
SCM-1500S	220-240V ~ 50/60Hz	SMD2835	16.5 W	1500/1000/700 Lm 270 Lm	—	—	Yes	Φ335x63 mm
SCM-1500EL01	220-240V ~ 50/60Hz	SMD2835	16 W	1500/1000/700 Lm 270 Lm	1h	LiFePO ₄ 3.2V 1500mAh 18650MUB	—	Φ335x63 mm
SCM-1500EL03	220-240V ~ 50/60Hz	SMD2835	16.5 W	1500/1000/700 Lm 270 Lm	3h	LiFePO ₄ 3.2V 3000mAh 18650MUB	—	Φ335x63 mm
SCM-1500EL01S	220-240V ~ 50/60Hz	SMD2835	17.5 W	1500/1000/700 Lm 270 Lm	1h	LiFePO ₄ 3.2V 1500mAh 18650MUB	Yes	Φ335x63 mm
SCM-1500EL03S	220-240V ~ 50/60Hz	SMD2835	18 W	1500/1000/700 Lm 270 Lm	3h	LiFePO ₄ 3.2V 3000mAh 18650MUB	Yes	Φ335x63 mm

*SCM-1500EL01-ST --- Emergency version with self-testing function
 SCM-1500-DA --- DALI version
 SCM-1500-DU --- Dual colour temperature version
 SCM-1500-PH --- Built-in Photocell version
 SCM-1500-BL --- Bluetooth version

Emergency Lumen
 Parameter tolerance: ±10%
 CCT: 4000K



IoT by Zigbee Version



Code	Input Voltage	LED Type	Input Power	Lumen	Duration	Battery	Dimensions (LxWxH)	Functions
SCN-900-BC	220-240V ~ 50/60Hz	SMD2835	9 W	900 Lm	—	—	Φ267x57 mm	Brightness Control, CCT Control
SCN-900-BCS	220-240V ~ 50/60Hz	SMD2835	10.5 W	900 Lm	—	—	Φ267x57 mm	Brightness Control, CCT Control, Sensor
SCN-900-BCC	220-240V ~ 50/60Hz	SMD2835	9.5 W	900 Lm	—	—	Φ267x57 mm	Brightness Control, CCT Control, Constant Brightness
SCM-1500-BC	220-240V ~ 50/60Hz	SMD2835	15 W	1500 Lm	—	—	Φ335x63 mm	Brightness Control, CCT Control
SCM-1500-BCS	220-240V ~ 50/60Hz	SMD2835	10.5 W	1500 Lm	—	—	Φ335x63 mm	Brightness Control, CCT Control, Sensor
SCM-1500-BCC	220-240V ~ 50/60Hz	SMD2835	15.5 W	1500 Lm	—	—	Φ335x63 mm	Brightness Control, CCT Control, Constant Brightness
SCM-1500-BCEL01	220-240V ~ 50/60Hz	SMD2835	16 W	1500 Lm 270 Lm	1h	LiFePO ₄ 3.2V 1500mAh 18650MUB	Φ335x63 mm	Brightness Control, CCT Control, Emergency
SCM-1500-BCEL03	220-240V ~ 50/60Hz	SMD2835	16.5 W	1500 Lm 270 Lm	3h	LiFePO ₄ 3.2V 3000mAh 18650MUB	Φ335x63 mm	Brightness Control, CCT Control, Emergency
SCM-1500-BCEL01S	220-240V ~ 50/60Hz	SMD2835	17.5 W	1500 Lm 270 Lm	1h	LiFePO ₄ 3.2V 1500mAh 18650MUB	Φ335x63 mm	Brightness Control, CCT Control, Emergency, Sensor
SCM-1500-BCEL03S	220-240V ~ 50/60Hz	SMD2835	18 W	1500 Lm 270 Lm	3h	LiFePO ₄ 3.2V 3000mAh 18650MUB	Φ335x63 mm	Brightness Control, CCT Control, Emergency, Sensor

Emergency Lumen
 Parameter tolerance: ±10%
 CCT: 4000K

APPLICATION

- Houses
- Offices
- Retail
- Schools
- Hotels
- Hospitals



Modulized Lighting Engine

- Easy Installation
- Easy Replacing



Modulized Emergency Kit

- Easy Installation
- Easy Replacing
- With LiFeP04 Battery

